






Type	Description / Technical data	Picture
MCS-AY-D12	<p><b>Proximity (contactless) card reader</b></p> <p>Proximity reader for indoor applications. White plastic housing with LED &amp; buzzer indicator, back-tamper function. Reading range: up to 100mm; Operating range: 0 ~ +45 °C; Current consumption: standby 35mA / reading 50mA; Dimensions (HxWxD): 122x75x24 mm; For indoor application only.</p>	
MCS-MSR-262	<p><b>Magnetic Stripe Slot Reader</b></p> <p>Magnetic stripe reader for magnetic stripe cards. Black plastic housing with LED indicator. Operating range: 0 ~ +45 °C; Current consumption: 30mA; Dimensions (HxWxD): 100x31x32 mm; For indoor application only.</p>	
MCS-BCR-250	<p><b>Barcode Slot Reader</b></p> <p>Barcode slot reader in black plastic housing with LED indicator. Operating range: 0 ~ +45 °C; Current consumption: 38mA; Dimensions (HxWxD): 100x31x32 mm; For indoor application only.</p>	
MCS-PCR-230	<p><b>Proximity (contactless) FRID Code Verifier</b></p> <p>Proximity reader Code Verifier for defining and verifying the Proximity (contactless) cards and tags. Keyboard PS2 interface for PC with "Y" connection cable for PC Keyboard &amp; Code Verifier to PC. White plastic housing with LED &amp; buzzer indicator. Reading range: up to 100mm; Operating range: 0 ~ +45 °C; Current consumption: 300mA; Dimensions (HxWxD): 134x38x65 mm; For indoor application only.</p>	
MCS-MSR-400	<p><b>Magnetic Stripe Code Verifier</b></p> <p>Magnetic stripe slot verifier for defining and verifying the magnetic stripe cards. Keyboard PS2 interface for PC with "Y" connection cable for PC Keyboard &amp; Code Verifier to PC. White plastic housing with LED &amp; buzzer indicator. Operating range: 0 ~ +45 °C; Current consumption: 80mA; Dimensions (HxWxD): 170x42x44 mm; For indoor application only.</p>	
MCS-BCR-431	<p><b>Barcode Code Verifier</b></p> <p>Barcode verifier for defining and verifying the barcodes cards. Keyboard PS2 interface for PC with "Y" connection cable for PC Keyboard &amp; Code Verifier to PC. White plastic housing with LED &amp; buzzer indicator. Operating range: 0 ~ +45 °C; Current consumption: 80mA; Dimensions (HxWxD): 170x42x44 mm; For indoor application only.</p>	