

Type	Description / Technical data	Picture
MCS-AC-C31	<p>Single Door PIN Controller – Keypad (500 codes)</p> <p>Stand alone, Single door PIN controller for 99/500 user codes; 2 System PIN codes; Operating range: -30° ~ +65 °C; Current consumption: standby 20mA / max 75mA; IP56; Dimensions (HxWxD): 130x42x18 mm; Operate only with external power supply MCS-PS-C15T. Indoor and outdoor application.</p>	
MCS-AC-063	<p>Single Door Proxy Controller – Keypad (99 codes)</p> <p>Stand alone, Single door Proxy controller for 99/500 user codes; 2 System PIN codes; Operating range: -30° ~ +65 °C; Current consumption: standby 20mA / max 75mA; IP56; Dimensions (HxWxD): 130x42x18 mm; Operate only with external power supply MCS-PS-C15T. Indoor and outdoor application.</p>	
MCS-AYC-G64	<p>Single Door Proxy Controller – Keypad (500 codes)</p> <p>Stand alone, Single door Proxy controller for 500 user codes; 3 Security levels; Operating range: -30° ~ +65 °C; Current consumption: standby 105mA / max 140mA; IP65; Dimensions (HxWxD): 137x44x21 mm; Operate only with external power supply MCS-PS-C25T. Indoor and outdoor application.</p>	
MCS-AYC-Q54B	<p>Single Door PIN Controller – Keypad (500 codes)</p> <p>Stand alone, Weather & Vandal resistant Single door PIN controller for 500 user codes; Buttons keypad; Internal buzzer & 2 LED status indicators; Current consumption: standby 40mA / max 130mA; Operating range: -30° ~ +65°C; Dimensions (HxWxD): 120x76x27 mm; Operate with external power supply MCS-PS-C25T. Outdoor & Indoor applications.</p>	
MCS-AYC-Q64B	<p>Single Door Proxy & PIN Controller – Keypad (500 codes)</p> <p>Stand alone, Weather & Vandal resistant Single door Proxy & PIN controller for 500 user codes; Buttons keypad; Internal buzzer & 2 LED status indicators; Current consumption: standby 40mA / max 130mA; Operating range: -30° ~ +65°C; Reading range: up to 65mm; Dimensions (HxWxD): 120x76x27 mm; Operate only with external power supply MCS-PS-C25T. Outdoor & Indoor applications.</p>	
MCS-AYC-E65B	<p>Single Door Proxy & PIN Controller + Keypad (piezoelectric)</p> <p>Stand alone, Vandal & Water resistant, fully sealed ultra-slim Single door Proxy & PIN controller for 500 user codes; outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Reading range: up to 40mm; Operating range: -30 ~ +65 °C; Current consumption: standby 92mA / reading 105mA; Dimensions (HxWxD): 155x44x9 mm; Operate only with external power supply MCS-PS-C25T. Ideal for special applications.</p>	
MCS-AYC-E55B	<p>Single Door PIN Controller – Keypad</p> <p>Stand alone, Vandal & Water resistant, fully sealed ultra-slim Single door PIN controller for 500 user codes; outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Operating range: -30 ~ +65 °C; Current consumption: standby 92mA / reading 105mA; Dimensions (HxWxD): 155x44x9 mm; Operate only with external power supply MCS-PS-C25T. Ideal for special applications.</p>	
MCS-PS-C15T MCS-PS-C25T	<p>Intelligent Power Supply – Metal Box</p> <p>Intelligent Power supply with transformer for single door controllers; Data line between the controller and power supply unit. Secured relay output for door lock; Speaker alarm output; Input: 230VAC~50Hz, 0.14A; Output: 16VAC~1.5A, 24VA; Fuse protection 1A. Space for 7Ah accumulator battery.</p>	